

## Narrow Body Semi-Automatic Strapping Machine

Introducing the new iQ-400NA2, StrapPack's new narrow body semi-automatic strapping machine with dual tension mode. This allows for a wide variety of applications with just a flick of a switch.



## iQ-400NA2

- The iQ-400NA2 is a durable and heavy-duty strapping machine designed to withstand various harsh environments.
- The iQ-400NA2 is yet amazingly quiet to operate and well suited for office use also.
- The iQ-400NA2 has less moving parts, which makes it easy to maintain and keeps the operation cost low.
- All electric parts are arranged in one side of the machine, enclosed in the cabinet, for easy maintenance and protection of crucial parts.
- The iQ-400NA2 runs strap from 5 millimeters to 15.5 millimeters (5/8 inches) without additional parts.
- The torque tension mode is suitable for stronger tension or to strap compressible packages, while the stroke tension mode is best for soft tension or quick operation.
- Tool-free access to frequently accessed areas for easy maintenance.
- Optional adjustable legs are available upon request. With this option, table height can be adjusted to 750, 800, 850 or 900mm.

<b>Dimension</b>	<b>Width</b>	580 mm	22-7/8 in.
	<b>Height</b>	775 mm(with work guide)	30-1/2 in.(with work guide)
	<b>Depth</b>	540 mm	21-1/4 in.
	<b>Weight</b>	43 kg.	95 lbs.
<b>Table Height</b>		750 mm	29-1/2 in.
<b>Min. Package Size</b>		W 100 X H 30 mm	W 3-1/8 X H 1-1/8 in.
<b>Joint / Strap/ Coil</b>		heat seal / polypropylene ID 200 X W 200 mm	heat seal / polypropylene 8 X 8 in.
<b>Strap Width / Thickness</b>		5, 6,9,12 (15.5) mm /0.45-0.7mm	1/4,3/8,1/2 (5/8) in./ 0.017-0.027 in.
<b>*Strap Tension</b>		*Max. 450N (45.9 kgf) or 150mm stroke	*Max. 101 lbf. or 5-7/8 in. stroke
<b>Power Supply</b>		100-120, 200-240 V 1 Phase 50 / 60 Hz 0.35 kW	

Dimensions and specifications are subject to change without notice.

Modification rights reserved.

© 2019 Strapack Corporation

### DISTRIBUTED BY:



ISO 9001 and 14001 Certified

STRAPACK CORPORATION  
 8-16-6 Ginza, Chuo-ku, Tokyo, 104-0061, JAPAN  
 Phone: 81-3-6278-1806 Fax: 81-3-6278-1807  
 (URL) <http://www.strapack.com> (E-mail) [info@strapack.com](mailto:info@strapack.com)  
 STRAPACK INC.  
 33508 Central Avenue, Union City, CA 94587-2097 U.S.A.  
 Phone :1-510-475-6000 Fax: 1-510-475-6090  
 STRAPACK, N.V./S.A.  
 Uilenbaan 200, B-2160 Wommelgem, BELGIUM  
 Phone: 32-3-355-1520 Fax: 32-3-355-1521